

	K2	(2) T8 8' lamps -or- (3 to 8) 4' T8 lamps and standard electronic ballast	\$80
T12 VHO	L Retrofit Very High Output Fixtures with T5 Lamps & Ballasts		
	<i>Includes lamp/ballast retrofits only; <u>Ballast</u>: PF ≥ 90%, THD < 20%. <u>Lamp</u>: 4' T5 HO. Lumen Maint. ≥ 90%, CRI ≥ 80, lamp life ≥ 20,000 hours, Initial System Lumens/Watt ≥ 80</i>		
	L1	2 T5 lamps and high output ballast	\$50
	L2	3 to 4 T5 lamps and high output ballast	\$100
Any Existing Condition	M Other "one time" measure with pre-approval from BPA		
	<i>Includes lighting measures that are not on the above list (A-L). One-time deemed credit/reimbursement can be given to measures that receive pre-approval from BPA.</i>		
Any Existing Condition	N Demonstration Technologies (Requires BPA pre-approval)		
	<i>Includes LED fixtures or screw-in lamps that have been approved by BPA.</i>		
	N1	LED Canopy lights with lumens per watt greater than 70	\$230
	N2	LED screw-in reflector lamp with lumens per watt greater than 40	\$20
Eligibility: Minimum project-wide kWh savings for incentives			25%

Program Offering for New Construction Projects

New Fixture/Sensor Description		Incentive
A. High-Performance T8 Fluorescent Lamps and Electronic Ballast in a New Fixture		
<i>The fixture shall include a High Performance 48" T8 lamp and ballast system listed on the CEE qualifying products list.</i>		
A1NC	Upgrade to High Performance T8 or NLO T5	\$10
B. High-Bay T8 or T5 Fluorescent New Fixture		
<i>T5 fixture must have 2 or more lamps, T8 fixture must have 3 or more lamps. Fixture must be installed in a high bay area</i>		
B1NC	T8 or T5 New "High Bay" Fixture	\$50